

Date :

2017/8/29



MORIMOTO Harness standard

品名	規格	直径(公差)	密度 intersection	荷重	構成	使用例
Item name	m/roll	ODmm (tolerance)	1cm density	sp tension	Composition of braid	Application example
thin MS - 103	2100 m/roll	φ 0.70 ± 0.05	19.0 pcs	< 30 g	core 6 %	necktie, homefabric, label
MS - 106CZ	2050 m/roll	φ 0.70 ± 0.05	19.0 pcs	< 45 g	core 6 %	necktie, homefabric, label * Carbon in
MS - 106	2000 m/roll	φ 0.75 ± 0.05	20.0 pcs	< 45 g	core 17 %	necktie, homefabric, label
MS - 203ZA	1700 m/roll	φ 0.80 ± 0.05	20.0 pcs	< 100 g	core 19 %	necktie, homefabric, label
MS - 205	1550 m/roll	φ 0.85 ± 0.05	20.0 pcs	< 100 g	core 13 %	airbag, carseat, homefabric, needle, towel
MS - 207	1200 m/roll	φ 0.95 ± 0.05	20.0 pcs	< 130 g	core 13 %	airbag, carseat, towel
MS - 303	650 m/roll	φ 1.40 ± 0.05	15.0 pcs	< 180 g	core 25 %	carpet, velvet
MS - 305	560 m/roll	φ 1.55 ± 0.05	15.0 pcs	< 180 g	core 28 %	carpet, velvet
thick MS - 403	450 m/roll	φ 1.85 ± 0.05	13.0 pcs	< 200 g	core 25 %	carpet, velvet